




**Pressure drop diagram:** Applies to size 592 x 592 x 600 mm/8 bags



**Bag filter MultiSack K95**

consists of synthetic fibre fleece

**Special features:**

The spacers ensure complete utilization of the full bag length; sealing of spacer seams; as compared to rated air-flow volume, operating air-flow volume can be increased by 25%, cone-shaped bags.

**Application:**

Fine particle filtration

**Areas of application:**

All HVAC and air handling installations with a filtration function.

**Type:**

designed in galvanized frame – surcharge for plastic frame on request.

**The recommended final pressure difference:**

250 Pa



**Frame material**

Plastic or galvanized

**Filter class as of EN 779:2012**

F8

**For the NEW filter class as of**

**ISO 16890:2016**  
ISO ePM1 75%


**Medium:**  
synthetic

**Temperature resistance**  
< 70 °C

**Energy class**  
E

**Fire Retardant Class acc. to DIN 4102-1**  
B2

*\* applies only to special sizes - check table*

 <b>Bag filter MultiSack K95</b> <b>Filter medium: Synthetic</b>		Width [mm]	Height [mm]	Depth [mm]	Number of bags [quantity]	Filtration surface [m <sup>2</sup> ]	Volume flow [m <sup>3</sup> /h]	Initial pressure drop [Pa]	Energy class certified by the Eurovent 4/21	<b>NEW filter class as of ISO 16890:2016</b>
1000739A	K95-6V/0600/08/05	592	592	600	8	6	3.400	173	E	ISO ePM <sub>1</sub> 75 %
1000734A	K95-5V/0600/06/05	490	592	600	6	4,4	2.800	173		
1000731A	K95-3V/0600/04/05	287	592	600	4	3	1.700	173		
1000729A	K95-2V/0600/04/05	287	287	600	4	1,5	850	173		
1000737A	K95-1V/0600/08/05	592	287	600	8	3	1.700	173		
1003584A	K95-6V/0534/08/05	592	592	534	8	5,2	3.400	164	E	ISO ePM <sub>1</sub> 75 %
1003578A	K95-5V/0534/06/05	490	592	534	6	3,9	2.800	164		
1003568A	K95-3V/0534/04/05	287	592	534	4	2,6	1.700	164		
1003559A	K95-2V/0534/04/05	287	287	534	4	1,3	850	164		
1003549A	K95-1V/0534/08/05	592	287	534	8	2,6	1.700	164		
1003583A	K95-6V/0380/08/05	592	592	380	8	3,9	3.400	220	E	ISO ePM <sub>1</sub> 75 %
1003577A	K95-5V/0380/06/05	490	592	380	6	2,9	2.800	220		
1003566A	K95-3V/0380/04/05	287	592	380	4	1,9	1.700	220		
1003557A	K95-2V/0380/04/05	287	287	380	4	0,9	850	220		
1003547A	K95-1V/0380/08/05	592	287	380	8	1,9	1.700	220		