

ATF 8 Speed

Description and Properties:

ATF 8 Speed - Fluid is an Automatic Transmission Fluid based on HC and PAO.

ATF 8 Speed affords following benefits:

- highest Quality Features
- high load capacity and extremely wear-reducing
- superior friction constant
- no foaming
- minimal evaporation losses
- excellent low-temperature switching behavior
- adapted friction characteristics, for sporty gear changes
- excellent oxidation and thermal stability
- no effect on usual sealing materials

Specification / Recommendations:

BMW L12108 (83 22 2 152 426)	Jaguar 02JDE 26444
BMW 83 22 2 305 397	Land Rover LR 023288
BMW 83 22 2 289 720	VW / Audi G 060 162 A1/A2/A6, G 055 162 (A2, A6)
Chrysler 68157995AA	ZF Lifeguardfluid 8 (S671 090 312)

Typical Values:

ATF 8 Speed	Unit	Value	Method
Density at 15	kg/m ³	844	DIN 51 757
Color		grün	
Viscosity at 40°C	mm ² /s	26,4	DIN 51 562
Viscosity at 100°C	mm ² /s	5,6	DIN 51 562
Viscosity Index		160	DIN ISO 2909
Flash Point	°C	226	DIN ISO 2592
Pourpoint	°C	-45	DIN ISO 3016

*Specification variations in these characteristics may occur. The instructions of manufacturer must be regarded.
Further information available by MSDS.*

Hengst SE

Nienkamp 55-85
48147 Münster
Germany
Tel.: +49 251 20202-0

